MIRROR IMAGE Teleprompters, inc



38 Years Serving You!

Introducing the new HDMI studio teleprompter...



Specifications - SF-15E

Viewable Size - 15 inch

Brightness - 1000 NTS

Signal Input - SVGA, NTSC, HDMI

Input Voltage - 110 VAC / 12 Volt

Resolution - 1024 x 768

Power Consumption - 30-35 Watts

Input Connector - 15-pin D-Type BNC, HDMI

Special Features - Scan-Reverse BNC Loop

Weight - 24lbs

SF-15E

HDMI-NTSC-SVGA Inputs

15" color LCD monitor with aluminum LCD cabinet. Weighs only 24 pounds!

Reverses images internally — no special equipment or software needed!

Features an all aluminum rigid trapezoid hood - no plastic here!

Our largest 21"x18" true 60/40 Beamsplitter mirror in a wide angle trapezoid shape. The mirror has an anti-reflectant coating on camera side. The top in the industry!

Features an adjustable height camera platform (specify when ordered)

The hood/mirror is vertically adjustable for centering the camera lens

This product works great with any camera or tripod/pedestal

No counter weight needed. Perfect balance every time!

All metal components with durable powdercoat finish. Extremely tough!

Luggage grade Cordura fabric rear lens-hood surround.

3-year conditional warranty

200 dealers worldwide and ready to serve you!





\$1895

Phone

920-232-0220

Fax 920-232-1225

Email

sales@teleprompters.com

www.teleprompters.com

SF-15E
STUDIO
PROMPTER

DE OND-SES
DE 10010
DE 1

Contact us today with any additional questions you may have

