

MIRROR IMAGE

Teleprompters, Inc

38 Years Serving You!



Broadcast quality SDI studio teleprompter...

SF-160

SDI (HD or SD)-HDMI-NTSC-SVGA Inputs



Specifications - SF-160

Viewable Size - 15 inch

Brightness - 1500 NTS

Signal Input - SDI (HD or SD),
NTSC, HDMI, SVGA

Input Voltage - 110 VAC / 12 Volt
DC

Resolution - 1080, 720, 576, 480

Power Consumption - 25 Watts

Input Connector - BNC-SDI, BNC-
NTSC, HDMI, SVGA

Special Features - Scan-Reverse
BNC Loop

Weight - 26lbs

Super bright 1500 NTS panel with SDI inputs.
Weighs only 26 pounds!

Reverses images internally -- no special
equipment or software needed!

Features an all aluminum rigid
trapezoid hood - no plastic here!

Our largest 21"x18" true 60/40 Beamsplitter
mirror in a wide angle trapezoid shape. The
mirror has an anti-reflectant coating on
camera side. The top in the industry!

Features an adjustable height camera platform
(specify when ordered)

The hood/mirror is vertically adjustable for
centering the camera lens

This product works great with any camera or
tripod/pedestal

No counter weight needed.
Perfect balance every time!

All metal components with durable powder-
coat finish. Extremely tough!

3-year conditional warranty

200 dealers worldwide and
ready to serve you!



\$2995

Phone

920-232-0220

Fax

920-232-1225

Email

sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have



Made in Oshkosh, Wisconsin - USA