



38 Years Serving You!

The best selling broadcast quality SDI studio teleprompter...



Specifications - SF-170

Viewable Size - 17 inch

Brightness - 1500 NTS

Signal Input - SDI (HD or SD),

NTSC, HDMI, SVGA

Input Voltage - 110 VAC / 12 Volt

Resolution - 1080, 720, 576, 480

Power Consumption - 45 Watts

Input Connector - BNC-SDI, BNC-NTSC, HDMI, SVGA

Special Features - Scan-Reverse BNC Loop

Weight - 27lbs

SF-170

SDI (HD or SD)-HDMI-NTSC-SVGA Inputs

Super bright 1500 NTS panel with SDI inputs. Weighs only 27 pounds!

Reverses images internally -- no special equipment or software needed!

Features an all aluminum rigid trapezoid hood - no plastic here!

Our largest 21"x18" true 60/40
Beamsplitter mirror in a wide angle
trapezoid shape. The mirror has an antireflectant coating on camera side.
The top in the industry!

Features an adjustable height camera platform (specify when ordered)

The hood/mirror is vertically adjustable for centering the camera lens

This product works great with any camera or tripod/pedestal

No counter weight needed. Perfect balance every time!

All metal components with durable powder-coat finish. Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!





\$3095



Phone 920-232-0220

Fax 920-232-1225

Email

sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have



Made in Oshkosh, Wisconsin - USA