



38 Years Serving You!

Our newest 17" - SDI ready podium Speechprompter...

Specifications - PT-170

Viewable Size - 17 inch

Brightness - 1500 NTS

Signal Input - SDI (HD or SD), NTSC, HDMI, SVGA

Input Voltage - 110 VAC / 12 Volt

Resolution - 1080, 720, 576, 480

Power Consumption - 45 Watts

Input Connector - BNC-SDI, BNC-NTSC, HDMI, SVGA

Special Features - Scan-Reverse BNC Loop

Weight - 25 lbs

SP-170

SDI-HDMI-NTSC-SVGA Inputs

A true "Pro" speech system with SUPER BRIGHT LCD monitors that feature SDI inputs. Give your speaker the ultimate advantage!

Reverses images internally -- no special equipment or software needed!

System includes two housings, monitors, pole, Beamsplitter mirrors and <u>adjustable</u> angle mirror holders

Beamsplitter mirrors are special coated and include radiused corners.

Mirror size is 12.75" x 10.0"

The top in the industry!

Mirrors are adjustable for you to tilt at the perfect angle and the reader height can be adjusted up to 6'6"

Monitors are placed on the floor and are protected by metal housing that "nest together" for easy probability

All metal components with durable powder-coat finish.

Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!





\$4695

Phone 920-232-0220

Fax

920-232-1225

Email sales@teleprompters.com

www.teleprompters.com

SP-170
SPEECH
PROMPTER

Contact us today with any additional questions you may have

