MIRROR IMAGE Teleprompters, inc



37 Years Serving You!

Free standing prompter with SDI inputs...



Specifications - FS-160 OS

Viewable Size - 15 inch

Brightness - 1500 NTS

Signal Input - SDI (HD or SD), NTSC, HDMI, SVGA

Input Voltage - 110 VAC / 12 Volt

Resolution - 1080, 720, 576, 480

Power Consumption - 25 Watts

Input Connector - BNC-SDI, BNC-NTSC, HDMI, SVGA

Special Features - Scan-Reverse BNC Loop

Weight - 17 lbs

FS-160 OS

SDI-HDMI-NTSC-SVGA Inputs

Features a Broadcast quality LCD monitor (with SDI inputs) and mirror assembly with its own tripod stand

Reverses images internally — NO special equipment or software needed!

Simply bring your existing camera and tripod in behind this stand/prompter head and start shooting

Perfect for remote locations or home studio. A studio feed can be sent to the prompter head as well - great for interviews.

Large 15"x18" true 60/40 Beamsplitter mirror in a wide angle trapezoid shape for HD cameras. The top in the industry!

"Light-tight" design will not allow light from rear of monitor

> No counter weight needed. Perfect balance every time!

All metal components with durable powdercoat finish. Extremely tough!

> Luggage grade Cordura fabric lens- hood surround

3-year conditional warranty

200 dealers worldwide and ready to serve you!



\$3595



Phone

920-232-0220

Fax

920-232-1225

Email

sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have



Made in Oshkosh, Wisconsin - USA