



### 38 Years Serving You!

### Introducing the new 17" SDI podium Speechprompter...

Specifications - SP-17ES

Viewable Size - 17 inch

Brightness - 1000 NTS

Signal Input - SDI, HDMI, SVGA, NTSC

Input Voltage - 110 VAC / 12 Volt DC

**Resolution - 1024 x 768** 

**Power Consumption** - 30-35 Watts

Input Connector - 15-pin D-Type BNC, HDMI

**Special Features** - Scan-Reverse BNC Loop

Weight - 25lbs

# SP-17ES

SDI-HDMI-NTSC-SVGA Inputs

## Give your speaker the ultimate advantage. A true professional tool!

New monitors reverse images internallyno special equipment or software needed!

System includes two housings, monitors, pole, Beamsplitter mirrors and holders

Beamsplitter mirrors are special coated and include radiused corners. Mirror size is 12.75" x 10.0" The top in the industry!

Mirrors are set at the perfect angle and reader height can be adjusted up to 6'6"

Monitors are placed on the floor and are protected by metal housings that "nest together" for easy probability

All metal components with durable powder-coat finish

Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!



\$1995

Phone

920-232-0220

Fax

920-232-1225

**Email** 

sales@teleprompters.com

www.teleprompters.com

SP-17ES
SP-17ES
SP-17ES

Contact us today with any additional questions you may have

