



## 38 Years Serving You!

## Introducing our BIGGEST SDI podium Speechprompter...



Specifications - SP-19ES

Viewable Size - 19 inch

Brightness - 1000 NTS

Signal Input - SDI, HDMI, SVGA, NTSC

Input Voltage - 110 VAC / 12 Volt

**Resolution** - 1024 x 768

**Power Consumption - 30-35** 

Input Connector - 15-pin D-Type

BNC, HDMİ

Special Features - Scan-Reverse

**BNC Loop** Weight - 28lbs SP-19ES

SDI-HDMI-NTSC-SVGA Inputs

Give your speaker the ultimate advantage. A true professional tool!

New monitors reverse images internallyno special equipment or software needed!

System includes two housings, monitors, pole, Beamsplitter mirrors and holders

Beamsplitter mirrors are special coated and include radiused corners. Mirror size is 15.5" x 12.75" The top in the industry!

Mirrors are set at the perfect angle and reader height can be adjusted up to 6'6"

Monitors are placed on the floor and are protected by metal housings that "nest together" for easy probability

All metal components with durable powder-coat finish

Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!



\$2195

**Phone** 

920-232-0220

Fax 920-232-1225

**Email** 

sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have

