



39 Years Serving You!

Introducing the new HDMI podium Speechprompter...



Specifications - SP-15H

Viewable Size - 15 inch

Brightness - 600 NTS

Signal Input - HDMI, SVGA, NTSC,

Input Voltage - 110 VAC / 12 Volt DC

Resolution - 1400 x 1050

Power Consumption - 30-35 Watts

Input Connector - HDMI, 15pin D-Type BNC

Special Features - Easy hook-up for multiple prompters

Weight - 24lbs



SP-15H

HDMI-NTSC-SVGA Inputs

Give your speaker the ultimate advantage. A true professional tool!

Easy hook-up for multiple prompters

Prompting software must reverse image. Script-Q prompting software Script-Q prompting software is available (not included in purchase)

System includes two housings, monitors, pole, Beamsplitter mirrors and holders

Beamsplitter mirrors are special coated and include radiused corners.

Mirror size is 12.75" x 10.0"

The top in the industry!

Mirrors are set at the perfect angle and reader height can be adjusted up to 6'6"

Monitors are placed on the floor and are protected by metal housings that "nest together" for easy probability

All metal components with durable powder-coat finish

Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!



\$1195

Phone 920-232-0220

Email

sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have

